
PIVOT P

Reversible $\begin{bmatrix} 9\\ 1.2 \\ 9\\ 1.2 \\ 9\\ 0.9 \\ 9.5$





Blockboard frame, plywood casing



Invisible pivot hinges satin chrome finish

STANDARD MEASURES

STANDARD MEASURES	Widths					Heights		Thic	Thickness		
Wall opening	70	80	85	90	100	205	210	6.3	8	10	
External frame	68	78	83	88	98	204	214	6.3	8	10	
Door opening	60	70	75	80	90	200	210	6.3	8	10	

PANEL

44 mm thickness hollow core panel, finger joint fir wood perimeter frame with honeycomb core. Edge-finished on four sides, in laminate, cashmere and lacquered finish.

FRAME

Made of 40 mm thickness blockboard. Laminate, cashmere and lacquered finish.

COVER PROFILES

Made of plywood, thickness 12x90 mm flat coplanar nonadjustable on hinge side, thickness 9x95x30 mm telescopic. Telescopic range 17 mm on one side only. Laminate, cashmere and lacquered finish.

OPENINGS 120°

Reversible in heights 200 and 210 cm. Coplanar side to pull.

HARDWARE

Invisible pivot hinges satin chrome finish.

DOOR LOCK

Mediana magnetic lock with encoding key "11", matt chrome finish with Venusdesign logo for swing version, sliding door with round handle and puller in matt chrome finish, free/ busy device (lock) on request.

GASKETS

Perimetric gasket on three sides, matching with texture effect, interior in Acoustic Memory Foam.

FRAMEWORK FOR INTERNAL WALL SLIDING DOOR

Made of wood and mdf, available for metal counterframe widths from 100 - 125 - 150 mm, with telescopic cover profiles on both sides in plywood.